

# F6P21

## Cartridge operated foam grease fire extinguisher



# PASTOR

### Feuerlöscher

SCHAUM 6 L 21A 75F

- SICHERUNGSLASCHE  
HERAUSZIEHEN**  
REMOVE SAFETY DEVICE
- ROTE HAUBE  
KRÄFTIG SCHLAGEN**  
STRIKE ACTIVATION CAP
- LÖSCHPISTOLE  
BETÄTIGEN**  
SQUEEZE NOZZLE PISTOL



Vorsicht bei spannungsführenden Anlagen.  
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Bei jeder Nutzung des behälterlosen Löscher spätestens alle 2 Jahre auf Funktionsfähigkeit überprüfen.  
Bei vielen Lösch-/Trennvorgängen verwenden, die mit der Lösung des Problems verbunden sind.

TEMPERATURBEREICH: -20°C / 50°C ZULASSUNGSNUMMER:

LÖSCHMATERIAL: 6,5 L Wasser + 1,5 L Porenlöscher TYP: 10/20

GEWICHT: 75 g 00

PASTOR DEUTSCHLAND 42261 Mann (BRW) Böhmerstr. 43 Deutschland MADE IN THE EU PASTOR DEUTSCHLAND.DE

# PASTOR DEUTSCHLAND

# F6P21

## Cartridge operated foam grease fire extinguisher



### TECHNICAL DATA

Type	F6P21
Design	Cartridge operated foam grease fire extinguisher
Extinguishing agent quantity	6 l
Extinguishing agent	Foam
Propellant	CO <sub>2</sub>
Extinguishing performance	21A / 75F
Extinguishing agents units	21A (6)
Functional range	-30°C - +60°C
Operating time	45-50 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable quality hose incl. extinguishing nozzle
Weight	Approx. 10.75 kg
Height	Approx. 559 mm
Diameter	Approx. 150 mm

- Cartridge operated fire extinguisher, for more sustainability
- High performance extinguishing agent for efficient fire-fighting
- REACH-compliant
- Maintenance-friendly premium appliance
- Glass fibre reinforced plastic fitting with push-button release
- M74-Threaded opening for best maintenance
- Intuitive handling with simple release mechanism
- Glass fibre reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV and weather-resistant hose with swivelling and adjustable special extinguishing nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating
- Internal corrosion-resistant propellant bottle
- Wall bracket and foot ring
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Frost-resistant down to -30°C

LMD: 29-03-24, 18:48

**PASTOR**  
DEUTSCHLAND



42781 Haan (NRW)  
Bahnhofstraße 48  
Deutschland

**MADE IN THE EU**  
**PASTOR-DEUTSCHLAND.DE**