

# K2 Steel

## Carbon dioxide fire extinguisher



# PASTOR DEUTSCHLAND

# K2 Steel

## Carbon dioxide fire extinguisher



### TECHNICAL DATA

Type	K2 Steel
Design	Carbon dioxide fire extinguisher
Extinguishing agent quantity	2 kg
Extinguishing agent	Carbon dioxide
Propellant	CO <sub>2</sub>
Extinguishing performance	34B
Extinguishing agents units	34B (2)
Functional range	-30°C - +60°C
Operating time	8-10 s
Throwing distance	3-4 m
Hose / nozzle	Snow horn
Weight	Approx. 6 kg
Height	Approx. 570 mm
Diameter	Approx. 103 mm

When using carbon dioxide, the user may be exposed to a risk of suffocation.

2 kg CO<sub>2</sub> extinguishers require at least 11 m<sup>2</sup> of free floor space.

5 kg CO<sub>2</sub> extinguishers require at least 27.5 m<sup>2</sup> of free floor space.

Further information can be found at  
Deutsche Gesetzliche Unfallversicherung e. V. (DGUV)

<https://publikationen.dguv.de/widgets/pdf/download/article/3573>



We recommend labelling with appropriate signs (according to DGUV 205-034).



- Carbon dioxide fire extinguisher, for clean fire fighting
- Durable brass push lever fitting
- Reinforced carrying handle with balanced carrying properties
- Intuitive handling with simple release mechanism
- The appliance is immediately ready for use when the locking pin is pulled out
- Metal clamping strap / Wall bracket
- UV-resistant, durable plastic components
- UV-weatherproof snow horn for optimal application of the extinguishing gas
- Steel container with UV-resistant, durable polyester resin powder coating
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Frost-resistant down to -30°C

LMD: 08-12-24, 17:11

**PASTOR**  
DEUTSCHLAND



42781 Haan (NRW)  
Bahnhofstraße 48  
Deutschland

**MADE IN THE EU**  
**PASTOR-DEUTSCHLAND.DE**