# **\$50-N2**

## Mobile cartridge operated foam extinguishing trolley









PASTOR DEUTSCHLAND

### **S50-N2**

#### Mobile cartridge operated foam extinguishing trolley





#### **TECHNICAL DATA**

S50-N2 Type Mobile Cartridge operated Design foam extinguishing trolley 50 I **Extinguishing agent quantity Extinguishing agent** AB Foam **Propellant** N, **Extinguishing performance** AIVB **Extinguishing agents units Functional range** +5°C - +60°C **Operating time** 48 s **Throwing distance** 8-10 m Hose / nozzle Flexible high-pressure hose

- Film-forming extinguishing foam, particularly suitable for class B fires
- Mobile extinguisher, in accordance with DIN EN 1866
- Sturdy chassis, stable stand, tilt-proof
- High-quality stainless steel container, corrosion-resistant, weather-resistant and durable coating
- Additional safety thanks to a built-in safety valve
- UV and weather-resistant, durable components
- Easy handling, designed for use by a single person
- Simple dosing of extinguishing agent
- High throw ranges for effective and safe firefighting
- Flexible high-pressure hose, 5 m
- Easy to maintain
- Suitable for electrical systems up to 1000V, minimum distance 1m
- Not frost-resistant

LMD: 29-03-24, 18:48

Weight

Height

Diameter





42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU

PASTOR-DEUTSCHLAND.DE

Approx. 81 kg

Approx. 1060 mm

Approx. 470 mm