

# SD6Z34 GREEN

## Stored pressure foam fire extinguisher



# PASTOR

### Feuerlöscher

SCHAUM 6 L 34A 144B

-  **SICHERUNGSTIFT  
ENTFERNEN**  
PULL OUT SAFETY PIN
-  **SCHLAUCH AUF DEN  
BRANDHERD RICHTEN**  
AIM NOZZLE AT BASE OF FIRE
-  **HEBEL  
BETÄTIGEN**  
SQUEEZE VALVE



Vorsicht bei spannungsführenden Anlagen.  
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Bei jeder Bedienung von betriebsfähigen Löscheinrichtungen alle 2 Jahre auf Funktionszustand überprüfen.  
Bei neuen Löscheinrichtungen und Ersatzteilen verwenden, die mit der Zulassung übereinstimmen.

TEMPERATURBEREICH:	-5°C / +40°C	TRENNMITTEL:	STICKSTOFF 15 bar/32°C
LEISTUNGSFÄHIGKEIT:	PASTOR FF 606	ZULASSUNGSNUMMER:	EP 19/20.001.00
PS:	20 bar	TYP:	SD6Z34 GREEN

**PASTOR** DEUTSCHLAND  
43781 Haan (NRW)  
Ruhohrstraße 48  
Deutschland  
MADE IN THE EU  
PASTOR DEUTSCHLAND DE

# PASTOR DEUTSCHLAND

# SD6Z34 GREEN

## Stored pressure foam fire extinguisher



### TECHNICAL DATA

Type	SD6Z34 GREEN
Design	Stored pressure foam fire extinguisher
Extinguishing agent quantity	6 l
Extinguishing agent	Foam / Fluorine-free
Propellant	N <sub>2</sub>
Extinguishing performance	34A / 144B
Extinguishing agents units	34A (10) / 144B (9)
Functional range	+5°C - +60°C
Operating time	40-45 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable hose incl. extinguishing nozzle with optimised foaming
Weight	Approx. 11 kg
Height	Approx. 590 mm
Diameter	Approx. 150 mm

- Stored pressure fire extinguisher, the budget device
- Fluorine-free foam / Extinguishing agent contains no PFAS additives
- High performance extinguishing agent for efficient fire-fighting
- REACH-compliant
- Glass fibre reinforced plastic fitting with push-button release
- Durable M30 brass fitting with test and filling valve
- Intuitive handling with simple release mechanism
- Glass fibre reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV and weather-resistant hose with swivelling and adjustable extinguishing gun, with special nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating and robust thermoplastic inner coating
- Wall bracket
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Not frost-resistant

LMD: 29-03-24, 18:48

**PASTOR**  
DEUTSCHLAND



42781 Haan (NRW)  
Bahnhofstraße 48  
Deutschland

**MADE IN THE EU**  
**PASTOR-DEUTSCHLAND.DE**