

W6P34

Cartridge operated water fire extinguisher



PASTOR

Feuerlöscher

WASSER 6 L 34A

-  **SICHERUNGSLASCHE
HERAUSZIEHEN**
REMOVE SAFETY DEVICE
-  **ROTE HAUBE
KRÄFTIG SCHLAGEN**
STRIKE ACTIVATION CAP
-  **LÖSCHPISTOLE
BETÄTIGEN**
SQUEEZE NOZZLE PISTOL



Vorsicht bei spannungsführenden Anlagen.
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Nach jeder Befüllung von herkömmlichen Löschern spätestens alle 2 Jahre auf Funktionstauglichkeit überprüfen.
Bei unklarer Lösch-/Trennfähigkeit und Ersatzteile verwenden, die mit der Erklärung übereinstimmen.

TEMPERATURBEREICH: -1°C/-60°C ZULASSUNGSRUMMER: 8F 84/20 00 103

LEBENSZEIT: 4,81 MONAT + 1,21 JAHRE TYP: W6P34

NETZGEWICHT: 79 g CO2

PASTOR DEUTSCHLAND 40781 Haas (NRW) Zuhornstraße 48 Deutschland PASTOR-DEUTSCHLAND.DE



PASTOR DEUTSCHLAND

W6P34

Cartridge operated water fire extinguisher



TECHNICAL DATA

Type	W6P34
Design	Cartridge operated water fire extinguisher
Extinguishing agent quantity	6 l
Extinguishing agent	Water / Fluorine-free
Propellant	CO ₂
Extinguishing performance	34A
Extinguishing agents units	34A (10)
Functional range	+5°C - +60°C
Operating time	45-50 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable quality hose incl. extinguishing nozzle
Weight	Approx. 10.75 kg
Height	Approx. 559 mm
Diameter	Approx. 150 mm

- Cartridge operated fire extinguisher, for more sustainability
- Fluorine-free / Extinguishing agent contains no PFAS additives
- High performance extinguishing agent for efficient fire-fighting
- REACH-compliant
- Maintenance-friendly premium appliance
- Glass fibre reinforced plastic fitting with push-button release
- M74-Threaded opening for best maintenance
- Intuitive handling with simple release mechanism
- Glass fibre reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV and weather-resistant hose with swivelling and adjustable special extinguishing nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating and robust thermoplastic inner coating
- Internal corrosion-resistant propellant bottle
- Wall bracket and foot ring
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Not frost-resistant

LMD: 29-03-24, 18:48

PASTOR
DEUTSCHLAND



42781 Haan (NRW)
Bahnhofstraße 48
Deutschland

MADE IN THE EU
PASTOR-DEUTSCHLAND.DE