

# WD9Z43

## Stored pressure water fire extinguisher



# PASTOR

**Feuerlöscher**  
WASSER 9 L 43A

-  **SICHERUNGSTIFT  
ENTFERNEN**  
PULL OUT SAFETY PIN
-  **SCHLAUCH AUF DEN  
BRANDHERD RICHTEN**  
AIM NOZZLE AT BASE OF FIRE
-  **HEBEL  
BETÄTIGEN**  
SQUEEZE VALVE



Vorsicht bei spannungsführenden Anlagen.  
Nur bis 1.000 Volt. Mindestabstand 1 Meter.

Bei jeder Handhabung des Inhaltlichen Löschers spätestens alle 2 Jahre auf Funktionsfähigkeit überprüfen.  
Bei einem Mangel/Funktionsstörung und Ersatzteile verwenden, die mit der Zulassung übereinstimmen.

TEMPERATURBEREICH: +5°C/-40°C TREIBMITTEL: Stickstoff 70 bar/70°C  
LÖSCHMITTEL: Wasser mit Zugschraube ZULASSUNGSRUMMER: W90043  
PULV: 20 bar 70°C

PASTOR DEUTSCHLAND 42791 Hepp (4000) Mühlentstraße 49, Deutschland MADE IN THE EU PASTOR-DEUTSCHLAND.de

# PASTOR DEUTSCHLAND

# WD9Z43

## Stored pressure water fire extinguisher



### TECHNICAL DATA

Type	WD9Z43
Design	Stored pressure water fire extinguisher
Extinguishing agent quantity	9 l
Extinguishing agent	Water
Propellant	N <sub>2</sub>
Extinguishing performance	43A
Extinguishing agents units	43A (12)
Functional range	0°C - +60°C
Operating time	54-56 s
Throwing distance	4-6 m
Hose / nozzle	Flexible, durable quality hose incl. extinguishing nozzle
Weight	Approx. 14.5 kg
Height	Approx. 640 mm
Diameter	Approx. 170 mm

- Stored pressure fire extinguisher, the budget device
- High performance extinguishing agent for efficient fire-fighting
- REACH-compliant
- Extinguishing agent contains no PFAS additives
- Durable M30 brass fitting with test and filling valve
- Intuitive handling with simple release mechanism
- When the locking pin is pulled the device is immediately ready for use
- Reinforced carrying handle with balanced carrying properties
- UV-resistant, durable plastic components
- UV weather-resistant hose with special nozzle for optimum discharge of the extinguishing agent
- Steel container with UV-resistant, durable polyester resin powder coating and robust thermoplastic inner coating
- Wall bracket
- Suitable for electrical systems up to 1000 volts, minimum distance 1 m
- Not frost-resistant

LMD: 29-03-24, 18:48

**PASTOR**  
DEUTSCHLAND



42781 Haan (NRW)  
Bahnhofstraße 48  
Deutschland

**MADE IN THE EU**  
**PASTOR-DEUTSCHLAND.DE**